

OpenSSH

Because SSH is amazing.

Tunneling

```
# Using connect-proxy as a socks proxy (tunneling ssh over http proxy to an
ssh server on port 1.2.3.4:443)
Host 1.2.3.4
  ProxyCommand connect-proxy -H proxy:3128 %h %p
  Port 443
  User shaun

# -W can be used for raw port-forwarding on OpenSSH 5.4 and higher
Host internal.server
  HostName internal.server.com
  User shaun
  ProxyCommand ssh shaun@intermediary.server.com -W %h:%p

# Here's the old way, with netcat
Host internal.server
  HostName internal.server.com
  User shaun
  ProxyCommand ssh shaun@intermediary.server.com nc %h %p

# New to OpenSSH 7.3 and higher is the ProxyJump command, which does the
same, but with multiple possible intermediaries
Host internal.server
  HostName internal.server.com
  ProxyJump shaun@intermediary1.server:22,shaun@intermediary2.server:22
  User shaun
```

Filesystems

[xfs](#)

[ext4 recovery](#)

Get detailed memory chip information

```
dmidecode --type 17
```

Sample output:

```
# dmidecode 2.12
SMBIOS 2.7 present.
```

Handle 0x003B, DMI type 17, 34 bytes

Memory Device

Array Handle: 0x002C
Error Information Handle: Not Provided
Total Width: 72 bits
Data Width: 64 bits
Size: 32 GB
Form Factor: DIMM
Set: None
Locator: D0
Bank Locator: /SYS/MB/P0
Type: DDR3
Type Detail: Synchronous
Speed: 1066 MHz
Manufacturer: Samsung
Serial Number: 366112E5
Asset Tag:
Part Number: M393B4G70BM0-YH9
Rank: 1
Configured Clock Speed: 1066 MHz

From:

<https://wiki.dewberry.co.za/> - Shaun's Wiki

Permanent link:

<https://wiki.dewberry.co.za/doku.php?id=linux&rev=1536657276>

Last update: 2019/09/16 16:09

