

OpenSSH

Because SSH is incredible.

Tunneling

```
# Using connect-proxy as a socks proxy (tunneling ssh over http proxy to an
ssh server on port 1.2.3.4:443)
Host 1.2.3.4
  ProxyCommand connect-proxy -H proxy:3128 %h %p
  Port 443
  User shaun

# -W can be used for raw port-forwarding on OpenSSH 5.4 and higher
Host internal.server
  HostName internal.server.com
  User shaun
  ProxyCommand ssh shaun@intermediary.server.com -W %h:%p

# Here's the old way, with netcat
Host internal.server
  HostName internal.server.com
  User shaun
  ProxyCommand ssh shaun@intermediary.server.com nc %h %p

# New to OpenSSH 7.3 and higher is the ProxyJump command, which does the
same, but with multiple possible intermediaries
Host internal.server
  HostName internal.server.com
  ProxyJump shaun@intermediary1.server:22,shaun@intermediary2.server:22
  User shaun
```

SSH as a VPN

```
ssh -NTcf -w 0:0 <destination>

# Machine A
ip link set tun0 up
ip addr add 10.0.0.100/32 peer 10.0.0.200 dev tun0

# Machine B
ip link set tun0 up
ip addr add 10.0.0.200/32 peer 10.0.0.100 dev tun0

# Add a route for target network on Machine B
ip route add 10.0.0.0/24 via 10.0.0.200
```

```
#This allows us to send packets from Machine B to any IP address on Network A, via Machine A.  
#To ensure that packets have a route back to Machine B add an arp entry on Machine A:  
  
arp -sD 10.0.0.200 eth0 pub  
  
#This sets a published arp destination for 10.0.0.200 to Machine A (proxy-ARP).  
  
# Kernel packet forwarding must be enabled for the routing bits  
echo 1 | sudo tee /proc/sys/net/ipv4/ip_forward
```

Copy and install public key

```
ssh-copy-id -i .ssh/id_rsa.pub user@server.com
```

Filesystems

[xfs](#)
[ext4 recovery](#)

Get detailed memory chip information

```
dmidecode --type 17
```

Sample output:

```
# dmidecode 2.12  
SMBIOS 2.7 present.  
  
Handle 0x003B, DMI type 17, 34 bytes  
Memory Device  
    Array Handle: 0x002C  
    Error Information Handle: Not Provided  
    Total Width: 72 bits  
    Data Width: 64 bits  
    Size: 32 GB  
    Form Factor: DIMM  
    Set: None  
    Locator: D0  
    Bank Locator: /SYS/MB/P0  
    Type: DDR3  
    Type Detail: Synchronous  
    Speed: 1066 MHz  
    Manufacturer: Samsung  
    Serial Number: 366112E5
```

```
Asset Tag:  
Part Number: M393B4G70BM0-YH9  
Rank: 1  
Configured Clock Speed: 1066 MHz
```

OpenSSL

Convert .crt to .pem

```
openssl x509 -in certificate.crt -out certificate.pem -outform PEM
```

Other

Conceal process in 'ps'

```
echo FakeProcName > /tmp/cmdline  
mount -n --bind -o ro /tmp/cmdline /proc/<pid>/cmdline  
  
ps -ef | grep FakeProcName
```

[Oracle Enterprise Linux](#)

From:
<https://wiki.dewberry.co.za/> - **Shaun's Wiki**

Permanent link:
<https://wiki.dewberry.co.za/doku.php?id=linux&rev=1537433923>

Last update: **2019/09/16 16:10**

