

Custom scripts

drive_down_checker.ksh

```
#!/bin/ksh
#-----
# Check drives, bring drive up if down, email
# If drives are up, do not create a report, runs from cron
#-----
# Add interested parties below:
alert_mail=mail@mydomain.co.za
/usr/opensv/volmgr/bin/vmopr cmd -d ds | grep "DOWN" >/dev/null
if [ $? -ne 1 ];then
    rm /tmp/drivelog
    /bin/date >> /tmp/drivelog

    echo "" >> /tmp/drivelog
    for i in `usr/opensv/volmgr/bin/vmopr cmd -d ds | tail -n +5 |
grep "DOWN"|awk '{print $1}'`
    do
        echo -e "Drive $i is in DOWN status, bringing drive UP\n" >>
/tmp/drivelog
        /usr/opensv/volmgr/bin/vmopr cmd -up $i
    done
/usr/opensv/volmgr/bin/vmopr cmd -d ds >> /tmp/drivelog
cat /tmp/drivelog | /bin/mail -s "Drive(s) outages on `hostname`" \
    $alert_mail
fi
```

From:

<https://wiki.dewberry.co.za/> - Shaun's Wiki

Permanent link:

<https://wiki.dewberry.co.za/doku.php?id=netbackup&rev=1534927711>

Last update: 2019/09/16 16:10

